

CSP-600EZ Series Hi-Res CCD Color Camera

EZ-MOUNT 600TVL HIGH PERFORMANCE INDUSTRIAL GRADE I/R ARMOR DOME, LIGHTNING & SURGE PROTECTED

MODELS

CSP-600EZ 1/3" SONY SuperHAD2™ CCD

GENERAL

Sensor Type	1/3-inch Sony Super HAD2™ CCD
Effective Pixels	768 (H) x 494 (V)
Scanning System	2:1 Interlace
Horizontal Resolution	600TVLines
Electronic Shutter	Auto
Lens	3.6mm Fixed
Minimum Illumination	0 Lux (IR on)
S/N Ratio	>50dB
Automatic Gain Control	Auto
Video Output	1.0Vp-p Composite Video, 75 Ohms
White Balance Mode	Auto
IR LED	24 IR LEDs
IR Distance	20m Indoor, 15m Outdoor
Sync System	Internal
AGC	Auto
Day/Night	Auto

ELECTRICAL

Power Requirements	Regulated 12V±1 DC
Power Consumption	200mA (IR off) 450mA (IR on)
Power Connector	2.1 x 5.5, center positive
Video Connector	BNC

MECHANICAL

Lens Type	Internal 3.6mm
-----------	----------------



ENVIRONMENTAL

Operating Temperature	-4° to 122°F (-20° to 50°C)
Storage Temperature	-4° to 140°F (-20° to 60°C)
Operating Humidity	90% RH Max.
System Rating	IP66

PHYSICAL

Dimensions	86mm (Height) x 118mm (Base Diameter)
Weight	1 lb approx.
Shipping Weight	1.5 lbs approx.

OPTIONAL ACCESSORIES