

## GV- Hub



The GV-Hub adds 4 RS-232 and 4 RS-485 serial ports to your PC's USB port. The USB solutions for serial port extension is perfect for mobile instrumentation and POS applications.

### Specifications

Serial Interface	RS-232	Signal:	DCD, R x D, T x D, DTR, GND, DSR, RTS, CTS
		Connector:	4 x DB9 Male (A, B, C, D)
	RS-485	Signal:	D+, D-, GND
		Connector:	4 x Terminal Block (A, B, C, D)
	Serial Line Protection	16 KV ESD for All Signals	
USB	Compliance	USB 1.1, 1.0	
		USB 2.0 Backward Compatible	
	Speed	Full Speed 12 Mbps	
Communication	Parity	None, Even, Odd	
	Data Bit	7, 8	
	Stop Bit	1, 2	
	Flow Control	RTS / CTS, XON / XOFF	
	Speed	600 bps to 115,200 bps	
Environmental Conditions	Operation temperature	0~55°C / 32~131°F	
	Humidity	5%~95% (non-condensing)	
OS Supported	Windows XP / Windows Vista / Windows 7 / Windows Server 2008		
Dimensions(W x H x D)	103 x 30 x 125 (mm) / 4.06 x 1.18 x 4.92 (in)		
Installation Guide	<a href="#">GV-Hub</a>		