

GV-NET/IO Card V3.1



The GV-NET/IO card provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages and provides a USB port as well.

Specifications					
Input	Input	4			
	Input Signal	Dry-Contact Wet-Contact : 9~30V AC/DC			
Output	Relay Output	4			
	Relay Status	Normal Open			
	Relay Capacitance	<table border="0"> <tr> <td>USB Connection</td> <td>30V DC, 3A</td> </tr> <tr> <td>RS-232 Connection</td> <td>125 / 250V AC, 3A 30V DC, 3A</td> </tr> </table>	USB Connection	30V DC, 3A	RS-232 Connection
USB Connection	30V DC, 3A				
RS-232 Connection	125 / 250V AC, 3A 30V DC, 3A				
Interface		RJ-11 to DB9			
		RJ-11 to USB			
		3-pin internal USB to internal USB			
Mode Switch	I/O Box Mode	Without GV-Video Capture Card			
	NET/IO Card Mode	With GV-Video Capture Card			
Address		1-4			
Communication		RS-485, USB, RS-232			
Environmental Conditions		0~50°C / 32~122°F , 5%~95% (non-condensing)			
OS Supported	32-bit	Windows XP / Windows Vista / Windows 7 / Windows Server 2008			
	64-bit	Windows 7 / Windows Server 2008 (Only for PC's COM port connection)			
Dimensions (W x H)		90 x 99 (mm) / 3.90 x 3.54 (in)			
Installation Guide		GV-NET/IO Card V3.1			